

ACTIV'LIGHT™

TIGER® BRAND SHD-GC
TRAILING CABLES





INDEX

36-502	ACTIV'LIGHT 2kV Type SHD-GC • TPU Jacket	1
36-514	ACTIV'LIGHT 5kV Type SHD-GC • TPU Jacket	1
36-518	ACTIV'LIGHT 8kV Type SHD-GC • TPU Jacket	2-3
36-521	ACTIV'LIGHT 15kV Type SHD-GC • TPU Jacket	2-3
36-526	ACTIV'LIGHT 25kV Type SHD-GC • TPU Jacket	4


ACTIV'LIGHT JACKET OVERVIEW

- ACTIV'LIGHT's clear TPU jacket is designed for extremely abrasive environments. Compared to Tiger® Brand CPE jackets, TPU offers:
 - **5X** more abrasion resistance
 - **2X** more tear resistance and tensile strength
 - Up to **8% less** jacket weight
- Heavy-duty high-voltage portable power cable for use in circuits not exceeding the rated voltage.
- Recommended maximum continuous conductor temperature 90°C.
- Available in 2kV - 25kV.



Made in America

Tiger® Brand is a registered trademark of AmerCable Incorporated



The High Visibility of ACTIV'LIGHT Helps Prevent Runover Incidents



Available with RED or WHITE LED Lights



36-502/14

ACTIV'LIGHT 2KV - 5KV • TYPE SHD-GC



Fillers

LED Assembly

Shielded single with energy harvesting tape for illumination, and fillers as required. White LED lights are standard.

Assembly

Mylar taped core with clear TPU fillers

Ground Wires (2)

Flexible tinned copper

Ground Check Conductor

Flexible tinned copper with yellow polypropylene insulation

Conductors (3)

- Flexible tinned copper
- Non-conducting tape
- Insulation: 90°C ethylene-propylene rubber (EPR)
- Separator tape
- Insulation shielding composed of tinned copper and color-coded nylon braid.

Jacket¹

Clear Thermoplastic Polyurethane (TPU) Jacket. Cable identification via permanent marking.

APPLICATION

Heavy duty portable power cable for use in circuits not to exceed recommended voltage. Designed for applications such as shovels and powerfeeders where grounding conductors, a ground check conductor and metallic shielding are required.

ACTIV'LIGHT uses induced voltage to light up the cable during mining activity. This higher level of visibility helps prevent runovers and costly downtime.

Recommended maximum continuous conductor temperature is 90°C.


Tiger® Brand cables meet or exceed ICEA Standard S-75-381/NEMA WC-58.

RATINGS & APPROVALS

ACTIV'LIGHT LED lighting is an add-on to Tiger® Brand mining cables, which are compliant to:

- Mine Safety & Health Administration 184-MSHA
- Pennsylvania Department of Environmental Protection P-184.
- Insulated Cable Engineers Association S-75-381/NEMA WC-58. Design standard for mining cables.

Available in White (standard) or Red LEDs.



2000 VOLT 36-502 SHD-GC

36-502-	Power Conductors		Grounds	Jacket Thickness in.	Ground Check Conductor Size AWG	Nominal Outside Dimensions in.	Approx. Weight lbs. per 1,000 ft.	Ampacity*
	Size AWG or kcmil	Insulation Thickness in.	Size AWG					
250LED	250	0.095	1/0	0.220	6	2.985	6007	355
350LED	350	0.095	2/0	0.235	6	3.280	7491	435
500LED	500	0.095	4/0	0.265	6	3.595	9997	536

5000 VOLT 36-514 SHD-GC

36-514-	Power Conductors		Grounds	Jacket Thickness in.	Ground Check Conductor Size AWG	Nominal Outside Dimensions in.	Approx. Weight lbs. per 1,000 ft.	Ampacity*
	Size AWG or kcmil	Insulation Thickness in.	Size AWG					
040LED	4/0	0.110	1	0.235	8	3.030	5723	321
250LED	250	0.120	1/0	0.250	6	3.165	6419	355
350LED	350	0.120	2/0	0.265	6	3.510	8017	435
500LED	500	0.120	4/0	0.280	6	3.785	10199	536

¹ All cables have clear TPU jacket.

*Ampacity – Based on continuous duty at 90°C conductor temperature and 40°C ambient.



36-518/21

ACTIV'LIGHT 8KV - 15KV • TYPE SHD-GC

Fillers

LED Assembly

Shielded single with energy harvesting tape for illumination, and fillers as required. White LED lights are standard.

Assembly

Mylar taped core with clear TPU fillers

Ground Wires (2)

Flexible tinned copper

Ground Check Conductor

Flexible tinned copper with yellow polypropylene insulation



Conductors (3)

- Flexible tinned copper
- Strand shield: semi-conducting layer
- Insulation: 90°C ethylene-propylene rubber (EPR)
- Insulation shielding: semi-conducting tape
- Tinned copper and color-coded nylon braid

Jacket¹

Clear Thermoplastic Polyurethane (TPU) Jacket. Cable identification via permanent marking.

APPLICATION

Heavy duty portable power cable for use in circuits not to exceed recommended voltage. Designed for applications such as shovels and powerfeeders where grounding conductors, a ground check conductor and metallic shielding are required.

ACTIV'LIGHT uses induced voltage to light up the cable during mining activity. This higher level of visibility helps prevent runovers and costly downtime.

Recommended maximum continuous conductor temperature is 90°C.


Tiger® Brand cables meet or exceed ICEA Standard S-75-381/NEMA WC-58.

RATINGS & APPROVALS

ACTIV'LIGHT LED lighting is an add-on to Tiger® Brand mining cables, which are compliant to:

- Mine Safety & Health Administration 184-MSHA
- Pennsylvania Department of Environmental Protection P-184.
- Insulated Cable Engineers Association S-75-381/NEMA WC-58. Design standard for mining cables.

Available in White (standard) or Red LEDs.



**8000 VOLT
36-518
SHD-GC**

36-518-	Power Conductors		Grounds	Jacket Thickness in.	Ground Check Conductor Size AWG	Nominal Outside Dimensions in.	Approx. Weight lbs. per 1,000 ft.	Ampacity*
	Size AWG or kcmil	Insulation Thickness in.	Size AWG					
020LED	2/0	0.150	3	0.235	8	3.001	4657	243
030LED	3/0	0.150	2	0.250	8	3.050	5326	279
040LED	4/0	0.150	1	0.250	8	3.265	6155	321
250LED	250	0.150	1/0	0.250	6	3.325	6829	355
350LED	350	0.150	2/0	0.280	6	3.640	8391	435
500 LED	500	0.150	4/0	0.295	6	3.985	11198	536

**15000 VOLT
36-521
SHD-GC**

36-521-	Power Conductors		Grounds	Jacket Thickness in.	Ground Check Conductor Size AWG	Nominal Outside Dimensions in.	Approx. Weight lbs. per 1,000 ft.	Ampacity*
	Size AWG or kcmil	Insulation Thickness in.	Size AWG					
010LED	1/0	0.210	4	0.250	8	3.160	5185	215
020LED	2/0	0.210	3	0.250	8	3.230	5276	246
030LED	3/0	0.210	2	0.265	8	3.390	6226	283
040LED	4/0	0.210	1	0.265	6	3.570	7291	325
250LED	250	0.210	1/0	0.265	6	3.715	8062	359
350LED	350	0.210	2/0	0.280	6	3.925	9794	437
500LED	500	0.210	4/0	0.295	6	4.225	11594	534

¹ All cables have clear TPU jacket.

*Ampacity – Based on continuous duty at 90°C conductor temperature and 40°C ambient.



**Higher Visibility
at Night Helps
Prevent Runovers**



36-526

ACTIV'LIGHT 25KV • TYPE SHD-GC

Fillers

LED Assembly

Shielded single with energy harvesting tape for illumination, and fillers as required. White LED lights are standard.

Assembly

Mylar taped core with clear TPU fillers

Ground Wires (2)

Flexible tinned copper

Ground Check Conductor

Flexible tinned copper with yellow polypropylene insulation



Conductors (3)

- Flexible tinned copper
- Strand shield: semi-conducting layer
- Insulation: 90°C ethylene-propylene rubber (EPR)
- Insulation shielding: semi-conducting rubber and semi-conducting tape
- Tinned copper and color-coded nylon braid

Jacket¹

Clear Thermoplastic Polyurethane (TPU) Jacket. Cable identification via permanent marking.

APPLICATION

Heavy duty portable power cable for use in circuits not to exceed recommended voltage. Designed for applications such as shovels and powerfeeders where grounding conductors, a ground check conductor and metallic shielding are required.

ACTIV'LIGHT uses induced voltage to light up the cable during mining activity. This higher level of visibility helps prevent runovers and costly downtime.


Recommended maximum continuous conductor temperature is 90°C.

Tiger® Brand cables meet or exceed ICEA Standard S-75-381/NEMA WC-58.

RATINGS & APPROVALS

ACTIV'LIGHT LED lighting is an add-on to Tiger® Brand mining cables, which are compliant to:

- Mine Safety & Health Administration 184-MSHA
- Pennsylvania Department of Environmental Protection P-184.
- Insulated Cable Engineers Association S-75-381/NEMA WC-58. Design standard for mining cables.



Available in White (standard) or Red LEDs.

36-526-	Power Conductors		Grounds	Jacket Thickness in.	Ground Check Conductor Size AWG	Nominal Outside Dimensions in.	Approx. Weight lbs. per 1,000 ft.	Ampacity*
	Size AWG or kcmil	Insulation Thickness in.	Size AWG					
010LED	1/0	0.295	4	0.265	8	3.600	6229	218
020LED	2/0	0.295	3	0.280	8	3.680	6711	249
030LED	3/0	0.295	2	0.280	8	3.825	7462	286
040LED	4/0	0.295	1	0.295	6	3.975	7743	327
250LED	250	0.295	1/0	0.295	6	4.075	8500	360
350LED	350	0.295	2/0	0.295	6	4.390	10625	439

¹ All cables have clear TPU jacket.

*Ampacity – Based on continuous duty at 90°C conductor temperature and 40°C ambient.

FACTORY INSTALLED CABLE ASSEMBLIES



- Lower Overall Cost
- Enhanced Reliability
- Reduced Installation Time

Your cable assembly, built to your exact specifications, arrives ready for immediate use. Reduced prep, handling and installation time and no need to maintain an expensive connector inventory.

TRAINING, EDUCATION & SUPPORT



Our mine-experienced field engineers are available 24/7 for on-site evaluation and productivity solutions. They also conduct education and training sessions that address safety, splicing and cable handling practices.

No other cable manufacturer offers this high level of value and solutions!

ACTIV'LIGHT™

TIGER® BRAND SHD-GC TRAILING CABLES



Since the electrification of mines, our company's core business has been powering mine equipment.

Surface or underground – Nexans AmerCable has a cable productivity solution for you. Our innovatively engineered and manufactured Tiger® Brand cable line is designed for your toughest conditions.

ACTIV'LIGHT is the latest in a long line of cable innovations designed to enhance mine safety and productivity.

OPERATING EXCELLENCE

- Best at On-Time delivery
- Strategically located inventories throughout the major mining regions
- ISO-9001 certified manufacturer



ASK US ABOUT

ACTIV'LIGHT™

MINE POWER FEEDER

Nexans AmerCable

350 Bailey Road • El Dorado, Arkansas USA
(870) 862-4919 • (800) 643-1516 • Fax (870) 862-9613

e-mail: mining.sales@nexans.com

www.AmerCable.nexans.com

© 2020, AmerCable Incorporated 9_20

FOLLOW US!

